







Venturi	Part No.	Nozzle	Rated Pressure		Max Pressure		Max Vol.	Max Temp.
		mm	bar	p.s.i.	bar	p.s.i.	l/min	° C
54 AU NZ  G 3/8 M-M (adjustable)	E21.0150.18	1.8						
	E21.0150.21	2.1	220	3200	250	3650	30	90
	E21.0150.23	2.3						
	E21.0002.51	Nozzle 1.8						
	E21.0004.51	Nozzle 2.1						
E21.0007.51	Nozzle 1.5							
E21.0152.24	Repair kit							
55 AU NZ  G 3/8 F-M (adjustable)	E21.0015.18	1.8						
	E21.0015.21	2.1						
	E21.0170.18	1.8	220	3200	250	3650	30	90
	E21.0170.21	2.1						
	E21.0170.23	2.3						
E21.0002.51	Nozzle 1.8							
E21.0004.51	Nozzle 2.1							
E21.0007.51	Nozzle 1.5							
E21.0152.24	Repair kit							
56 AU  G 3/8 MxM22 (adjustable)	E21.0180.21	2.1	220	3200	250	3650	30	90
57 AU  M22 x 1.5 F-M (fixed)	E21.0035.18	1.8	220	3200	250	3650	30	90








Venturi		Part No.	Nozzle	Rated Pressure		Max Pressure		Max Vol.	Max Temp.
			mm	bar	p.s.i.	bar	p.s.i.	l/min	° C
58	AU NZ	E21.0120.21	2.1	350	5100	390	5650	30	90





Nozzle	thread size	spray angle	nozzle size(s)	
59 AU NZ	Stainless Steel 	1/8"	00° 025 030 035	060 065 070 075
		1/4"	25° 40° 045 050 055	080 085 090 100
60 AU NZ	Ceramic Insert 	1/8"	00° 15° 25°	080 087 093
		1/4"	40° 65° 062 068 074	099 111 124
61 AU NZ	Dump (brass) 	1/4" BSP	Dump	AU Part No. WL DUMP NZ Part No. CJ00819/A
		1/8" BSP	Dump	Part No. CJ00819

Nozzle	thread size	spray angle	nozzle size(s)	
62 NZ 	Quick Couple	0°		
63 NZ 	Quick Couple	15°	030 035 040 045	065 070 075 080
64 NZ 	Quick Couple	25°	050 055 060	085 090 100
65 NZ 	Quick Couple	40°		
66 NZ Dump (quick couple) 	Quick Couple	Dump	Part No. BE85.266.400	



NOZZLE SIZE SELECTION CHART										
Ceramic Nozzle	Stainless Steel Nozzle	Orifice (mm)	BAR	PRESSURE						
				70	100	135	150	200	275	345
				1000	1450	2000	2175	2900	4000	5000
	020	0.91	Litres per minute	3.8	4.6	5.3	5.6	6.4	7.6	8.5
037	030	1.10		5.7	6.8	7.9	8.4	9.7	11.3	12.6
049	040	1.30		7.6	9.1	10.6	11.2	12.9	15.1	16.9
056	045	1.35		8.6	10.3	11.9	12.6	14.5	17.0	19.1
062	050	1.40		9.5	11.4	13.2	14.0	16.1	18.9	21.2
068	055	1.50		10.5	12.5	14.6	15.4	17.7	20.8	23.3
074	060	1.60		11.4	13.7	15.9	16.7	19.3	22.7	25.4
080	065	1.65		12.4	14.8	17.2	18.1	21.0	24.6	27.5
087	070	1.70		13.3	16.0	18.5	19.5	23.0	26.5	29.6
093	075	1.75		14.3	17.1	19.9	21.0	24.0	28.3	31.8
099	080	1.80		15.3	18.2	21.2	22.0	26.0	30.2	33.9
-	085	1.85		16.2	19.4	22.5	24.0	27.0	32.1	36.0
111	090	1.90		17.2	21.0	23.8	25.0	29.0	34.0	38.1
124	100	2.00		19.1	23.0	26.5	28.0	32.0	37.8	42.3

Nozzles		Part No.	Max Press.		Max Vol. l/min	Sizes		Temp (°C)
			bar	p.s.i.		Inlet	Outlet	
67 AU NZ	 TR1 Nozzle Holder	E22.0000.00	280	4050	30	G1/4	1/4 NptF	160
		E22.0000.15	280	4050	30	G1/4	1/8 NptF	160
68 AU NZ	 TR4 Nozzle Holder	E22.0100.00	280	4050	30	G1/4 (Bsp) F	1/4 NPT F	160
69 NZ	 VAN 250	E25.0850.16	280	4050	40	G1/4F	053	90
70 AU NZ	 VANBY	E25.1010.10	250	3650	40	G1/4F	025	80
		E25.1010.11	250	3650	40	G1/4F	03	80
		E25.1010.12	250	3650	40	G1/4F	035	80
		E25.1010.13	250	3650	40	G1/4F	04	80
		E25.1010.14	250	3650	40	G1/4F	045	80
		E25.1010.15	250	3650	40	G1/4F	055	80

Nozzles		Part No.	Max Press.		Max Vol.	Sizes		Temp
			bar	p.s.i.	l/min	Inlet	Outlet	(°C)
71		IP ZREG	200	3000	21	G1/4F	135	60
AU							140	
NZ							145	
							150	
							155	
160								
165								
170								
175								
72	 TPR 50 Adjustable	M0204001210	210	3000	-	G1/4F	1/8	150
NZ							Npt F	
Sand Blasting Nozzles								
73	 Flat nozzle TS12	E25.0450.00	560	8100	80	G1/4F	1/4	90
AU								
NZ	 Straight nozzle	E25.0460.00						
74	 TS8	E25.0000.12	280	4050	40	G 1/4 (Bsp) F	03	90
AU		E25.0000.14	280	4050	40		04	90
NZ		E25.0000.15	280	4050	40		045	90
		E25.0000.18	280	4050	40		075	90
75	 Sand blasting head	PZTESABO	70/	1000/	8/5	G 1/4 F	-	-
AU			200	3000				
NZ								
76	 Sand poker	PZTESOND	-	-	-	Accesorie for sand blasting head above.	-	-
AU								
NZ								

Nozzles		Part No.	Max Press.		Max Vol.	Sizes		Temp
			bar	p.s.i.	l/min	Inlet	Outlet	(°C)
77 AU NZ	TS 33 professional sand blasting lance 	M0202903480	250	3600	40	M22x 1.5M	Nozzle 135	150
78 AU NZ	 ACID Lance	NPN2430	-	-	10:1 water ratio	Use with Gun/ Extention E30.2098 .00	-	-
Rotating Nozzles (Turbo Nozzle)								
79 AU NZ	 UR1	E25.1100.11 E25.1100.12 E25.1100.13 E25.1100.15	390 390 390 390	5650 5650 5650 5650	30 30 30 30	1/4 NPT M	03 035 04 35	80
80 AU NZ	 UR3	E25.1150.11	560	8100	80	G 1/2 F	06	80






Nozzles	Part No.	Max Press.		Max Vol.	Sizes		Temp	
		bar	p.s.i.	l/min	Inlet	Nozzle	(°C)	
Rotating Nozzles (Turbo Nozzle)								
81 NZ	 UR9	E25.1400.13	220	3200	-	G1/4 (Bsp) F	045	80
82 AU NZ	 ROTOJET 5000 PSI	M0204006900 M0204006905 M0204006910 M0204006915 M0204006920 M0204006925 M0204006930 M0204006935 M0204006940 M0204006945 M0204006950 M0204006960 M0204006970 M0204006980 M0204006990	350	5000	-	G1/4 F	030 035 040 045 050 055 060 065 070 075 080 090 10 11 12	100
83 AU NZ	 ROTOJET 3000 PSI	M0204007320 M0204007330 M0204007340 M0204007350 M0204007360 M0204007370 M0204007380	210	3000	-	G1/4 F	030 035 040 045 050 055 060	100
Drain Cleaning Nozzles								
84 NZ		I Drain Reg	200	3000	60	G3/8M	-	-
85 NZ		I Micro Drain 1	250	3500	19.5	G1/8F	-	-
86 AU NZ		E25.1201.51	250	3600	-	G1/4M	-	-
		E25.1210.51	250	3600	-	G3/8M	-	-

Nozzles	Part No.	Max Press.		Max Vol.	Sizes		Temp
		bar	p.s.i.	l/min	Inlet	Nozzle	(°C)
Steam Nozzles							
87 AU	 E25.2201.35	100	1450	-	G1/4(Bsp)F	-	130
Change over Nozzles							
88 AU NZ	 TD1 E23.0000.00 E23.0000.50	220	3200	40	G1/4(Bsp)F	1/4 NPT F 1/8 NPT F	90






Quick Couplings	Part No.	Max Press.		Inlet	Max Vol.	Max Temp
		bar	p.s.i.		l/min	(°C)
89 AU NZ	 ROTATING QUICK COUPLING MG	M0212000020 M0212000030 M0212000040 M0212000050	250	3600	40	130
NZ	HP2423.01 HP2423.03 HP2423.00 HP2423.02	3/8 G F 1/4 G F 3/8 G M 1/4 G M				
90 AU NZ	 ROTATING NIPPLE MG (with O ring)	M0212000120 M0212000130 M0212000140 M0212000150	250	3600	40	130
NZ	HP2423.05 HP2423.07 HP2423.04 HP2423.06	3/8 G F 1/4 G F 3/8 G M 1/4 G M				
91 AU NZ	 QUICK COUPLING MV (with single O ring)	M0212003520 M0212003530 M0212003540 M0212003550	250	3600	40	130
NZ		3/8 G F 1/4 G F 3/8 G M 1/4 G M				
92 AU NZ	 NIPPLE MV	M0212003620 M0212003630 M0212003640 M0212003650	250	3600	40	130
NZ		3/8 G F 1/4 G F 3/8 G M 1/4 G M				

Quick Couplings		Part No.	Max Press.		Inlet	Max Vol. l/min	Max Temp (°C)
			bar	p.s.i.			
93 AU NZ	 SCREW QUICK COUPLING (with single O & backup ring) AR1	E26.0250.20 E26.0250.30 E26.0250.40 E26.0250.50 E26.0250.60 E26.0250.70	250	3600	G 1/4F G 1/4M G 3/8M G 3/8M G 1/2F G 1/2M	40	160
94 AU NZ	 SCREW QUICK NIPPLE	E26.0051.31 E26.0033.31 E26.0002.31 E26.0030.31 E26.0031.31 E26.0032.31	250	3600	G 1/4M G 1/2F G 1/4F G 3/8M G 3/8F G 1/2M	40	160
95 AU	 SCREW QUICK NIPPLE AR3	E26.0205.00	250	3600	G 1/4F	40	160
96 AU	 SCREW QUICK COUPLING AR3	E26.0200.31	250	3600	G 1/4F	40	160
97 AU NZ	 SCREW QUICK NIPPLE AR5	E26.1034.50 E26.1034.00 E26.1033.00 E26.1034.20	250	3600	G 1/4M G 3/8M G 3/8M G 1/4F	40	160
98 AU NZ	 SCREW QUICK COUPLING (with 2 O rings) AR5	E26.1032.31 E26.1037.31 E26.1019.31 E26.1020.31	250	3600	G 1/4F G 3/8F G 3/8M G 1/4M	40	160

Quick Couplings		Part No.	Max Press.		Inlet	Max Vol.	Max Temp
			bar	p.s.i.		l/min	(°C)
99	 <p>SCREW QUICK NIPPLE M27</p>	E26.0460.50	120	1750	G 1/4F	30	60
100 NZ	 <p>SCREW QUICK COUPLING M27</p>	E26.0450.00	120	1750	G 1/4F	30	60
101	 <p>SCREW QUICK COUPLING Bayonet Holder</p>	E26.0605.00	120	1750	G 1/4F	30	90
102	 <p>SCREW QUICK NIPPLE M22</p>	E26.0055.00	280	4050	2xM22x1,5M	40	160

Snap Couplings		Part No.	Max Press.		Inlet	Max Vol. l/min	Max Temp (°C)
			bar	p.s.i.			
103	 SNAP COUPLING ARS150	E26.2010.00 E26.2010.10 E26.2010.20 E26.2010.30	150	2200	3/8 G M 3/8 G F 1/4 G F 1/2 G F	30	90
104	 NIPPLE ARS150	E26.2016.61 E26.2015.61 E26.2023.61	150	2200	1/4 G F 3/8 G F 3/8 G M	30	90
105	 SNAP COUPLING ARS220	E26.2030.00	220	3200	3/8 G F	50	90
106	 NIPPLE ARS220	E26.2035.61	220	3200	3/8 G F	50	90
107	 BRASS 	BE85.300.103 BE85.300.108 BE85.300.102 BE85.300.107 BE85.300.104 BE85.300.105 BE85.300.101 BE85.300.109	-	-	3/8 G F 3/8 G M 1/4 G F * 1/4 G M 3/8 G F 3/8 G M 1/4 G F * 1/4 G M	-	-

* Available in Stainless steel. AU only.

Swivels		Part No.	Max Press.		Max Vol.	Inlet	Temp (°C)
			bar	p.s.i.	l/min		
108 AU NZ	SW90 (90° Swivel) 	E26.1300.20	250	3650	40	1/4 G M-F	90
		E26.1300.40	250	3650	40	3/8 G M-F	90
109 AU NZ	MR-0 (Brass Swivel) 	E26.1040.00	250	3650	40	1/4 G M-F	160
		E26.1050.00	250	3650	40	3/8 G M-F	160
		E26.1055.00	250	3650	40	1/2 G M-F	160
110 AU NZ	LR (Light Resistance Swivel) 	E26.1000.00	220	3200	30	3/8 G M-F	90
111 AU NZ	MR-I (Stainless Steel Swivel) 	E26.1061.00	350	5100	40	3/8 G M-F	160
112 AU	MR-I 	M0212006000	220	3200	40	3/8 M	150